

WhisperFlo® High Performance Pumps

Energy Efficient Swimming Pool Pumps



WhisperFlo High Performance Pumps

Robust thermoplastic with the Cam & Ramp™ “see thru” lid design. Self-priming, high flow with Funnel-Flo™ diffusers. 2 in. suction and discharge ports. Motor features threaded shaft and durable commercial duty 56 frame motor with NEMA square flange.

Featured Highlights

- Oversized strainer basket and volute – industry standard in pool pumps
- Standard and Energy-efficient Square Flange Motors available
- Lower HP's deliver higher performance than industry standard
- Compatible with all cleaning systems, various filters and jet action spas
- Heavy-duty/durable construction is designed for long life
- Designed for residential and commercial applications
- New motor increases life, energy, efficiency, ease of installation and better cooling for long service life

Ordering Information

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt. (Lbs.)	Curve Key
ENERGY EFFICIENT SINGLE SPEED FULL RATED										
011511	WFE-2	115/208-230	8.8/4.5-4.4	1/2	1.90	0.95	UL ¹ , NSF ²	2 in. x 2 in.	41	E
011512	WFE-3	115/208-230	11.2/6.0-5.6	3/4	1.67	1.25	UL ¹ , NSF ²	2 in. x 2 in.	41	F
011513	WFE-4	115/208-230	14.8/7.8-7.4	1	1.65	1.65	UL ¹ , NSF ²	2 in. x 2 in.	46	G
011514	WFE-6	208-230	9.6-8.8	1-1/2	1.47	2.20	UL ¹ , NSF ²	2 in. x 2 in.	54	H
011515	WFE-8	208-230	11.0-10.2	2	1.30	2.60	UL ¹ , NSF ²	2 in. x 2 in.	55	I
011516	WFE-12	208-230	15.0-13.6	3	1.15	3.45	UL ¹ , NSF ²	2 in. x 2 in.	56	J
ENERGY EFFICIENT SINGLE SPEED UP RATED										
011517	WFE-24	115/208-230	11.2/6.0-5.6	1	1.25	1.25	UL ¹ , NSF ²	2 in. x 2 in.	41	F
011518	WFE-26	115/208-230	14.8/7.8-7.4	1-1/2	1.10	1.65	UL ¹ , NSF ²	2 in. x 2 in.	46	G
011519	WFE-28	208-230	9.6-8.8	2	1.10	2.20	UL ¹ , NSF ²	2 in. x 2 in.	54	H
011520	WFE-30	208-230	11.0-10.2	2-1/2	1.04	2.60	UL ¹ , NSF ²	2 in. x 2 in.	55	I
STANDARD EFFICIENCY SINGLE SPEED FULL RATED										
011578	WF-2	115/230	10.8/5.4	1/2	1.95	0.95	UL ¹ , NSF ²	2 in. x 2 in.	41	E
011579	WF-3	115/230	14.2/7.1	3/4	1.67	1.25	UL ¹ , NSF ²	2 in. x 2 in.	41	F
011580	WF-4	115/230	16.0/8.0	1	1.65	1.65	UL ¹ , NSF ²	2 in. x 2 in.	46	G
011581	WF-6	115/230	22.4/11.2	1-1/2	1.50	2.25	UL ¹ , NSF ²	2 in. x 2 in.	54	H
011582	WF-8	230	11.5	2	1.30	2.60	UL ¹ , NSF ²	2 in. x 2 in.	55	I
011583	WF-12	230	14.1	3	1.15	3.45	UL ¹ , NSF ²	2 in. x 2 in.	56	J
STANDARD EFFICIENCY SINGLE SPEED UP RATED										
011771	WF-23	115/230	10.8/5.4	3/4	1.24	0.93	UL ¹ , NSF ²	2 in. x 2 in.	41	E
011772	WF-24	115/230	14.2/7.1	1	1.24	1.24	UL ¹ , NSF ²	2 in. x 2 in.	41	F
011773	WF-26	115/230	16.0/8.0	1-1/2	1.10	1.65	UL ¹ , NSF ²	2 in. x 2 in.	46	G
011774	WF-28	115/230	22.4/11.2	2	1.10	2.20	UL ¹ , NSF ²	2 in. x 2 in.	54	H
011775	WF-30	230	11.5	2-1/2	1.04	2.60	UL ¹ , NSF ²	2 in. x 2 in.	55	I
ENERGY EFFICIENT SINGLE SPEED FULL RATED- 3 PHASE										
340061	WFK-2	208-230/460	3.2-3.0/1.5	1/2	1.90	0.95	NSF ²	2 in. x 2 in.	39	E
011021	WFK-3	208-230/460	3.8-3.6/1.8	3/4	1.65	1.25	NSF ²	2 in. x 2 in.	42	F
011568	WFK-4	208-230/460	5.0-4.6/2.3	1	1.65	1.65	NSF ²	2 in. x 2 in.	46	G
011569	WFK-6	208-230/460	6.4-5.8/2.9	1-1/2	1.47	2.20	NSF ²	2 in. x 2 in.	54	H
011570	WFK-8	208-230/460	7.1-6.8/3.4	2	1.30	2.60	NSF ²	2 in. x 2 in.	56	I
011571	WFK-12	208-230/460	11.0-10.4/5.2	3	1.15	3.45	NSF ²	2 in. x 2 in.	58	J

WhisperFlo® High Performance Pumps (Cont'd)

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt. (Lbs.)	Curve Key
ENERGY EFFICIENT TWO SPEED 3450 RPM, LOW SPEED 1725 RPM FULL RATED										
012530	WFDS-3	115	14.6/4.7	3/4	1.67	1.25	UL ¹ , NSF ²	2 in. x 2 in.	42	A, F
011486	WFDS-4	230	7.8/3.0	1	1.65	1.65	UL ¹ , NSF ²	2 in. x 2 in.	47	B, G
011522	WFDS-6	230	10.0/3.5	1-1/2	1.47	2.20	UL ¹ , NSF ²	2 in. x 2 in.	55	C, H
011523	WFDS-8	230	11.0/4.0	2	1.30	2.60	UL ¹ , NSF ²	2 in. x 2 in.	56	D, I
ENERGY EFFICIENT TWO SPEED 3450 RPM, LOW SPEED 1725 RPM UP RATED										
012485	WFDS-24	115	14.6/4.7	1	1.25	1.25	UL ¹ , NSF ²	2 in. x 2 in.	42	A, F
012518	WFDS-26	230	7.8/3.0	1-1/2	1.10	1.65	UL ¹ , NSF ²	2 in. x 2 in.	47	B, G
011524	WFDS-28	230	10.0/3.5	2	1.10	2.20	UL ¹ , NSF ²	2 in. x 2 in.	55	C, H
011525	WFDS-30	230	11.0/4.0	2-1/2	1.04	2.60	UL ¹ , NSF ²	2 in. x 2 in.	56	D, I
ACCESSORIES										
11201-0154	2 in. x 2 in. Union (2 in. NPT male x 2 in. female NPT quick connect) * Note: two required per pump (sold individually)									
357156	Cover/Lid, Chemical Resistant, CAM & RAMP									



¹ 'UL' indicates that pump bears a UL mark signifying evaluation to U.S. Standards UL1081 for Permanently Connected Swimming Pool and Spa Pumps and to Canadian Standards CAN/CSA C22.2 No. 108-01 Liquid Pumps For Swimming Pools Only (Enclosure 3).

² 'NSF' indicates that pump bears a NSF mark signifying evaluation to NSF Standard 50 For Self-Priming Centrifugal Pumps For Swimming Pools, Spas and Hot Tubs.

³ Product may have been evaluated to other state and local regulatory standards. Listing status may change. Always confirm status with appropriate agency if in doubt.


Dimensions and Performance

Pentair Pool Products
Whisperflo Series Performance Curves



A - varying length:

- 1/2 & 3/4 hp = 24.469"
- 1 hp = 24.72"
- 1-1/2 hp = 25.22"
- 2 & 3 hp = 25.72"



See page 478-479 for replacement parts.